



STONEX

RC9

F1

F2

F3

F4

F5

F6

P

Q

W

E

R

T

Y

O

I

O

CAPS

L

A

S

D

F

G

H

J

K

L

2

X

C

V

B

N

M

F7

F8

F9

SPACE

SHIFT

F10

F11

F12

PaUp

7

8

9

PaDn

4

5

6

CE

ESC

1

2

3

USER

PRG

0

.

+

← OFF → ON

RC9 FIELD CONTROLLER

Technical Data



Technical features

RC9 FIELD CONTROLLER

Technical Specifications

Communication	via integrated radio modem
Control unit	
Display:	1/4 VGA (320*240 pixels), graphic colour LCD, illumination, touch screen
Keyboard:	62 keys (12 function keys, 40 alphanumeric keys), illumination
Interface:	RS232
Battery	
Type:	Lithium-Ion
Voltage:	7.4 V
Capacity:	1.9 Ah
Operating time:	typ. 8 h

Weights

Control Unit:	0.8 Kg
Battery:	0.1 Kg
Reflector pole adapter:	0.25 Kg
Environmental specifications	
Working temperature range:	-30°C to +50°C
Storage temperature range:	-40°C to +80°C
Dust / water (IEC 60529):	IP67
Waterproof (MIL-STD-810F)	temporary submersion to 1 m

STONEX EUROPE srl

Via Zucchi 1, 20900 Monza (MI) ITALY
+39 0392783008
www.stonex.it
info@stonex.it

